



Drawing for determining: setup point, hatch door pivot range, & angle of inclination

PREMIER LOFT LADDERS

Tel: 0845 9000 195 Fax: 01394 214413
email: sales@premierloftladders.co.uk
www.premierloftladders.co.uk

2 Dawson Drive, Trimley St Mary
Felkstone, Suffolk, IP11 0YW

ELECTRICALLY OPERATED WOODEN HATCHBOX

APERTURE LENGTH REFER TO NOTE 1	APERTURE WIDTH REFER TO NOTE 2	a REFER TO NOTE a	b REFER TO NOTE b	FLOOR TO CEILING HEIGHT UP TO 4300	MAXIMUM AVAILABLE HATCHBOX WIDTH (b) THIS FIGURE IS THE USUAL MAXIMUM, BUT SPECIAL CONSTRUCTION MAY BE AVAILABLE
1500	670	1480	685		915

1. APERTURE LENGTH VARIABLE
2. APERTURE WIDTH VARIABLE
 - a. THE USUAL FINISHED LENGTH IS 20MM UNDER YOUR CHOSEN LENGTH
 - b. THE WIDTH IS VARIABLE BUT USUALLY FINISHES 15MM UNDER THE NOMINAL CHOSEN WIDTH, THE MINIMUM IS 630MM NOMINAL/615MM FINISH

TREAD NUMBERS FOR FLOOR TO CEILING HEIGHTS	FLOOR TO CEILING HEIGHT	NUMBER OF TREADS
UP TO 2500MM		9
2501 - 2790MM		10
2791 - 3090MM		11
3091 - 3390MM		12
3391 - 3690MM		13
3691 - 3990MM		14
3991 - 4300MM		15

REFER TO TREAD WIDTH GUIDE FOR HATCHBOX WIDTHS AND RESULTANT TREAD WIDTHS
TREAD MECHANISM SHOWN FOR ILLUSTRATIVE PURPOSES ONLY.
ALL DIMENSIONS IN MM
SCALE: 1:10. DATE: 06/11. ISSUE: A2
© All rights reserved Report all discrepancies Do not scale drawings