



Drawing for determining: setup point, hatch door pivot range, & angle of inclination

**PREMIER  
LOFT LADDERS**

2 Dawson Drive, Trimley St Mary  
Felixstowe, Suffolk. IP11 0YW

Tel: 0845 9000 195 Fax: 01394 214413  
email: sales@premierloftladders.co.uk  
www.premierloftladders.co.uk

**MINI: CONCERTINA LADDER**

APERTURE LENGTH REFER TO NOTE 1	APERTURE WIDTH REFER TO NOTE 2	a REFER TO NOTE a	b REFER TO NOTE b	FLOOR TO CEILING HEIGHT	MAXIMUM AVAILABLE HATCHBOX WIDTH (b) THIS FIGURE IS THE USUAL MAXIMUM, BUT SPECIAL CONSTRUCTION MAY BE AVAILABLE
1200	700	1185	685	UP TO 2500	700

1. APERTURE LENGTH VARIABLE
2. APERTURE WIDTH VARIABLE
  - a. THE USUAL FINISHED LENGTH IS 15MM UNDER NORMAL CHOSEN LENGTH
  - b. THE WIDTH IS VARIABLE BUT USUALLY FINISHES 15MM UNDER THE NOMINAL CHOSEN WIDTH, THE MINIMUM IS 700MM NOMINAL/685MM FINISH

REFER TO 'TREAD WIDTH GUIDE' FOR HATCHBOX WIDTHS AND RESULTANT TREAD WIDTHS

ALL DIMENSIONS IN MM  
© All rights reserved

SCALE: 1:10. DATE: 08/09. ISSUE: A1  
Report all discrepancies Do not scale drawings