



Hatch door Thickness = 62mm

Drawing for determining: setup point, hatch door pivot range, & angle of inclination

**PREMIER
LOFT LADDERS**

2 Dawson Drive, Trimley St Mary
Felixstowe, Suffolk. IP11 0YW
Tel: 0845 9000 195 Fax: 01394 214413
email: sales@premierloftladders.co.uk
www.premierloftladders.co.uk

ELECTRICALLY OPERATED WOODEN HATCHBOX

APERTURE LENGTH REFER TO NOTE 1	APERTURE WIDTH REFER TO NOTE 2	a REFER TO NOTE a	b REFER TO NOTE b	FLOOR TO CEILING HEIGHT	MAXIMUM AVAILABLE HATCHBOX WIDTH (b) THIS FIGURE IS THE USUAL MAXIMUM, BUT SPECIAL CONSTRUCTION MAY BE AVAILABLE
1500	670	1480	655	UP TO 4600	975

1. APERTURE LENGTH VARIABLE
2. APERTURE WIDTH VARIABLE
 - a. THE USUAL FINISHED LENGTH IS 15MM UNDER NORMAL CHOSEN LENGTH
 - b. THE WIDTH IS VARIABLE BUT USUALLY FINISHES 15MM UNDER THE NOMINAL CHOSEN WIDTH, THE MINIMUM IS 595MM NOMINAL/580MM FINISH

TREAD NUMBERS FOR FLOOR TO CEILING HEIGHTS	
FLOOR TO CEILING HEIGHT	NUMBER OF TREADS
UPTO 2500MM	9
2501 - 2790MM	10
2791 - 3090MM	11
3091 - 3390MM	12
3391 - 3690MM	13
3691 - 3990MM	14
3991 - 4300MM	15

REFER TO 'TREAD WIDTH GUIDE' FOR HATCHBOX WIDTHS AND RESULTANT TREAD WIDTHS
TREAD MECHANISM SHOWN FOR ILLUSTRATIVE PURPOSES ONLY.

ALL DIMENSIONS IN MM
Report all discrepancies

SCALE: 1:10. DATE: 01/10. ISSUE: A1
Do not scale drawings