



Supreme with steel hatchbox for flat roofs F30

Ready to install element
Safety tested: tested according to DIN EN 14975 by TÜV Süd

Thermal properties: U - Value lower cover F30 = 0.57 W/m² K
 Calculation of the isolated area according to DIN EN ISO 6946 by manufacturer

Stairs:
 Scissor unit: die-cast aluminium
 Load bearing capacity per tread 200 kg or 500 kg / m² of the entire component
 Tread depth 14 cm (16 cm)

Custom sizes:
 Custom sizes are available on request

Aperture length depends on the number of treads		Space required in cm		
Treads	Aperture size (length)	Floor to ceiling height "A"	Setdown point "B"	Swivel range "C"
9	100.5 - 150.5	220 - 250	120 - 115	126
10	100.5 - 150.5	250 - 279	130 - 124	137
11	100.5 - 150.5	279 - 309	140 - 133	147
12	100.5 - 150.5	309 - 339	150 - 142	157
13	130.5 - 150.5	339 - 369	176 - 169	182
14	140.5 - 150.5	369 - 399	187 - 180	193
15	150.5 - 150.5	399 - 430	198 - 190	205

Hatchbox external dimensions = aperture size - 2cm

Top cover thermal insulation values		
Insulation installed on site "D" max.	U-Value W/m ² K	Seal type
35 mm	1.1	Single seal
40 mm	0.68	Double seal
80 mm	0.38	Double seal
100 mm	0.31	Double seal



PREMIER LOFT LADDERS
 2 Dawson Drive,
 Trimley St Mary,
 Felixstowe, Suffolk. IP11 0YW
 Tel: 0845 9000 195
 Fax: 01394 214413
 www.premierloftladders.co.uk

Other sizes and different ceiling heights are available on request	6000215	Supreme with steel hatchbox for flat roofs, F30	Scale 1:10
--	---------	---	------------

The data on the drawings is for information only. All dimensions must be checked on site. No responsibility is taken for errors.

NOTE: ALL INFORMATION CONTAINED IN THIS DOCUMENT IS STRICTLY CONFIDENTIAL. THIS DRAWING IS THE PROPERTY OF PREMIER LOFT LADDERS AND MUST NOT BE REPRODUCED WITHOUT PRIOR PERMISSION.