



### Supreme with wooden hatchbox. 1 additional tread

**Ready to install element**

**Safety tested:** tested according to DIN EN 14975 by TÜV Süd

**Airtightness (a value):** class 4 - According to DIN EN 12114, DIN EN 1026, DIN EN 12207 by ift Rosenheim

**Thermal properties:** U - Value = 0.58 W/m<sup>2</sup> K according to EN ISO 12567-1 by ift Rosenheim

**Stairs:**

Scissor unit: die-cast aluminium  
Load bearing capacity per tread 200 kg or 500 kg / m<sup>2</sup> of the entire component  
Tread depth 14 cm (16 cm)

**Custom sizes:**

Custom sizes are available on request

Aperture length depends on the number of treads		Space required in cm		
Treads	Aperture size (length)	Floor to ceiling height "A"	Setdown point "B"	Swivel range "C"
9	90.5 - 160	220 - 250	127 - 113	136
10	90.5 - 160	250 - 279	136 - 122	147
11	100.5 - 160	279 - 309	146 - 130	158
12	100.5 - 160	309 - 339	155 - 138	169
13	130.5 - 160	339 - 369	181 - 166	195
14	140.5 - 160	369 - 399	191 - 176	207
15	150.5 - 160	399 - 430	202 - 185	220

Hatchbox external dimensions = aperture size - 1.5cm

Standard sizes	
Aperture size length x width	Tread width
120 x 60 cm	25 cm
120 x 70 cm	35 cm
130 x 70 cm	35 cm
140 x 70 cm	35 cm

NOTE: ALL INFORMATION CONTAINED IN THIS DOCUMENT IS STRICTLY CONFIDENTIAL. THIS DRAWING IS THE PROPERTY OF PREMIER LOFT LADDERS AND MUST NOT BE REPRODUCED WITHOUT PRIOR PERMISSION.



PREMIER LOFT LADDERS  
2 Dawson Drive,  
Trimley St Mary,  
Felixstowe, Suffolk. IP11 0YW  
www.premierloftladders.co.uk  
Tel: 0845 9000 195  
Fax: 01394 214413



Other sizes and different ceiling heights are available on request	6000222	Supreme with wooden hatchbox, 1 additional tread	Scale 1:10
--	---------	--	------------

The data on the drawings is for information only. All dimensions must be checked on site. No responsibility is taken for errors.