Customer requirements

Specification sheet:



Supreme stairway:

with a steel hatchbox and trapdoor F30, F60 and F90

Supreme stairway with a steel hatchbox and trapdoor F30

U-value 0.57 W/m² K. Ready to fit unit, with an aluminium concertina stairway attached to a steel hatchbox and steel trapdoor. The hatchbox is manufactured from 1.5mm steel and the trapdoor from 2 layers of 1.5mm steel infilled with 38mm of mineral wool. There is a 29mm wide lip to the bottom of the lining around the external edge, with a lip to the bottom of the steel trapdoor, which extends to within 15mm of the lip of the lining. Manufactured to EN14975 and has a load bearing per tread of 200kg. Fire resistance tested to DIN4102 Part 2.

Supreme stairway with a steel hatchbox and trapdoor F60 and F90

U-value 0.93 W/m² K. Ready to fit unit, with an aluminium concertina stairway attached to a steel hatchbox and steel trapdoor. The hatchbox is manufactured from 1.5mm steel and the trapdoor from 2 layers of 1.5mm steel infilled with 75mm of mineral wool. There is a 29mm wide lip to the bottom of the lining around the external edge, with a lip to the bottom of the steel trapdoor, which extends to within 15mm of the lip of the lining. Manufactured to EN14975 and has a load bearing per tread of 200kg. Fire resistance tested to DIN4102 Part 2.

Please see our website or request a brochure for full product details.



2 DAWSON DRIVE TRIMLEY St. MARY FELIXSTOWE SUFFOLK. IP11 OYW

TEL No.: 0845 9000 195 WWW.PREMIERLOFTLADDERS.CO.UK SALES@PREMIERLOFTLADDERS.CO.UK

Please forward a quotation to	@	based on the
Signed:		
Position:		