



Supreme DD

Ready to install element

Safety tested: Tested according to DIN EN 14975 by TÜV Süd

Airtightness (a value): class 4 - 600 pa pressure tested to DIN EN 12207 / 12144 by IFT Rosenheim

Thermal properties: U-Value = 0.29 W/m²K
Calculated by the manufacturer according to DIN ISO 6946

Stairs:

Scissor unit: Aluminium
Load bearing capacity per tread: 200kg or 500kg/m² of the entire component.
Tread depth: 14cm

Custom sizes:

Aperture length: 110cm - 160cm
Aperture width: 63cm - 80cm
Hatch box height: 63cm - 86.9cm

Electric operation:

Electric operation available. Minimum aperture sizes differ to those shown below.
Details available on request.

Aperture length depends on the number of treads		Space required in cm		
Treads	Aperture size (length)	Floor to ceiling height "A"	Setdown point "B"	Swivel range "C"
9	110 - 160	220 - 250	133 - 122	140
10	110 - 160	250 - 279	144 - 133	152
11	110 - 160	279 - 309	155 - 143	164
12	110 - 160	309 - 339	166 - 154	176
13	130 - 160	339 - 369	194 - 183	203
14	140 - 160	369 - 399	206 - 194	216
15	150 - 160	399 - 430	218 - 205	230

Hatchbox external dimensions = aperture size -2cm

PREMIER
LOFT=LADDERS

PREMIER LOFT LADDERS
2 Dawson Drive,
Trimley St Mary,
Felixstowe, Suffolk. IP11 0YW
Tel: 0345 9000 195
Fax: 01394 214413
www.premierloftladders.co.uk



© All rights reserved. Report all discrepancies. Do not scale drawings.

First Issue	Date	Name	Scale
A	05.2018	JP	1:10
B	07.2020	JP	AT A1
B	08.2022	JP	

Other sizes and different ceiling heights are available on request

7000201

Supreme with wooden hatchbox

The data on the drawings is for information only. All dimensions must be checked on site. No responsibility is taken for errors.