



Mini with wooden hatchbox

Ready to install element
Safety tested: tested according to DIN EN 14975 by TÜV Süd
Airtightness (a value): class 4 - 600pa pressure tested to DIN EN 12207 by ift Rosenheim
Thermal properties: U - Value lower cover = 0.8 W/m² K
 Calculation of the isolated area according to DIN EN ISO 6946 by manufacturer
Stairs:
 Scissor unit: Aluminium
 Treads: Aluminium profile
 Load bearing capacity per tread 150 kg or 350 kg / m² of the entire component
 Tread depth 8 cm
Custom sizes:
 Custom sizes are available on request

Aperture length depends on the number of treads		Space required in cm		
Treads	Aperture size (length)	Floor to ceiling height "A"	Setdown point "B"	Swivel range "C"
8	80 - 120	175 - 200	104 - 94	112
9	80 - 120	200 - 225	116 - 106	124
10	80 - 120	225 - 250	128 - 118	136
11	80 - 120	250 - 275	140 - 130	149
12	80 - 120	275 - 300	152 - 142	161
13	90 - 120	300 - 325	164 - 154	174

Hatchbox external dimensions = aperture size -1.5cm

Standard sizes			
Aperture size length x width	Floor to ceiling height "A"	Tread width	Hatchbox height
112 x 60 cm	225 - 275	33 cm	24 cm
112 x 70 cm	225 - 275	33 cm	24 cm
120 x 60 cm	225 - 275	33 cm	24 cm
120 x 70 cm	225 - 275	33 cm	24 cm

NOTE: ALL INFORMATION CONTAINED IN THIS DOCUMENT IS STRICTLY CONFIDENTIAL. THIS DRAWING IS THE PROPERTY OF PREMIER LOFT LADDERS AND MUST NOT BE REPRODUCED WITHOUT PRIOR PERMISSION.



PREMIER LOFT LADDERS
 2 Dawson Drive,
 Trimley St Mary,
 Felixstowe, Suffolk. IP11 0YW
 Tel: 0845 9000 195
 Fax: 01394 214413
 www.premierloftladders.co.uk

Other sizes and different ceiling heights are available on request	6000237	Mini with wooden hatchbox	Scale 1:10
--	---------	---------------------------	------------

The data on the drawings is for information only. All dimensions must be checked on site. No responsibility is taken for errors.