



Elite with high backboard

Ready to install element

Stairs:

Scissor unit: Aluminium

Load bearing capacity per tread: 200kg or 500kg/m² of the entire component.

Tread depth: 14cm (16cm)

Custom sizes:

Custom sizes are available on request. Please refer to custom width table below

Aperture length depends on the number of treads		Space required in cm	
Treads	Aperture size (length) min. cm	Floor to ceiling height "A"	Setdown point with $\alpha = 20^\circ$ "B"
9	70	220 - 250	109 - 118
10	75	250 - 279	120 - 128
11	83	279 - 309	130 - 139
12	90	309 - 339	141 - 150

Custom widths	
Aperture size (width) min. cm	Tread width
59	25
64	30
69	35

NOTE: ALL INFORMATION CONTAINED IN THIS DOCUMENT IS STRICTLY CONFIDENTIAL. THIS DRAWING IS THE PROPERTY OF PREMIER LOFT LADDERS AND MUST NOT BE REPRODUCED WITHOUT PRIOR PERMISSION.



PREMIER LOFT LADDERS
 2 Dawson Drive,
 Trimley St Mary,
 Felixstowe, Suffolk. IP11 0YW
 Tel: 0845 9000 195
 Fax: 01394 214413
 www.premierloftladders.co.uk

Other sizes and different ceiling heights are available on request	FRIST	Date	Name	Elite with high backboard	Scale
	ISSUE	26.09.2016	Ra		
6000419	A	08.08.2017	JP	The data on the drawings is for information only. All dimensions must be checked on site. No responsibility is taken for errors.	1:10
	Report all discrepancies				