



Ecco Concertina Loft Ladder

Ready to install element

Safety tested: tested according to DIN EN 14975 by TÜV Süd

Airtightness (a value): class 4 - 600pa pressure tested to DIN EN 12207 by ift Rosenheim

Thermal properties: U-Value lower cover = 0.77 W/m²K

Calculation of the isolated area according to DIN EN ISO 6946 by manufacturer

Stairs:

Scissor unit: Aluminium

Treads: Aluminium profile

Load bearing capacity per tread: 150kg or 350kg/m² of the entire component.

Tread depth: 8cm

Custom sizes:

Custom sizes are available on request

Aperture length depends on the number of treads		Space required in cm		
Treads	Aperture size (length)	Floor to ceiling height "A"	Setdown point "B"	Swivel range "C"
8	80 - 160	175 - 200	99 - 92	106
9	80 - 160	200 - 225	111 - 104	118
10	80 - 160	225 - 250	123 - 116	130
11	80 - 160	250 - 275	134 - 128	141
12	80 - 160	275 - 300	146 - 140	153
13	90 - 160	300 - 325	158 - 151	165

Hatchbox external dimensions = aperture size - 2 cm

Standard sizes			
Aperture size length x width	Floor to ceiling height "A"	Tread width	Hatchbox height
110 x 60 cm	225 - 275	33 cm	24 cm
110 x 70 cm	225 - 275	33 cm	24 cm
120 x 60 cm	225 - 275	33 cm	24 cm
120 x 70 cm	225 - 275	33 cm	24 cm



PREMIER LOFT LADDERS
2 Dawson Drive,
Trimley St Mary,
Felixstowe, Suffolk. IP11 0YW
Tel: 0845 9000 195
Fax: 01394 214413
www.premierloftladders.co.uk



© All rights reserved. Report all discrepancies. Do not scale drawings.

Other sizes and different ceiling heights are available on request	Date	Name	Ecco Concertina	Scale
				1:10

6000493
The data on the drawings is for information only. All dimensions must be checked on site. No responsibility is taken for errors.