



Steel Fire Rated Loft Hatch F30, F60, F90

Ready to install element

Thermal properties: U-Value lower cover F30 = 0.57 W/m²K. U-Value lower cover F60 & F90 = 0.93 W/m²K. Calculation of the isolated are according to EN ISO 6946 by manufacturer.

Fire Rating: F30 = 30 minutes protection from below. F60 = 60 minutes protection from below. F90 = 90 minutes protection from below. Certified to DIN4102-2 by MPA Stuttgart. Installation in steel reinforced concrete ceilings from 180mm thick.

Custom Sizes:

Aperture length: 780mm - 1600mm
 Aperture width: 595mm - 1300mm
 Hatch box height: 240mm - 1170mm

NOTE: ALL INFORMATION CONTAINED IN THIS DOCUMENT IS STRICTLY CONFIDENTIAL. THIS DRAWING IS THE PROPERTY OF PREMIER LOFT LADDERS AND MUST NOT BE REPRODUCED WITHOUT PRIOR PERMISSION.



PREMIER LOFT LADDERS
 2 Dawson Drive,
 Trimley St Mary,
 Felixstowe, Suffolk. IP11 0YW
 Tel: 0845 9000 195
 Fax: 01394 214413
 www.premierloftladders.co.uk



Other sizes and different ceiling heights are available on request	Date	Name	Steel Fire Rated Loft Hatch F30, F60, F90	Scale 1:10 AT A1
	09.05.2018	JP		
6000496		The data on the drawings is for information only. All dimensions must be checked on site. No responsibility is taken for errors.		