


Airtightness (a value): class 4 - 600pa pressure tested to DIN EN 12207 / 12144 by ift Rosenheim

Fire Rating: F30 = 30 minutes protection from below. F60 = 60 minutes protection from below. Certified to DIN4102-2 by MPA Braunschweig. Certified to DIN EN1365-2 / 1363-1. Installation in wood-beamed ceiling (≥ 197mm) or in concrete ceilings (≥150mm).


Aperture length (F30, F30 Plus): 750mm - 1500mm
Aperture length (F60): 750mm - 1400mm
Aperture width (F30, F30 Plus): 550mm - 900mm
Aperture width (F60): 550mm - 700mm
Hatch box height: 220mm - 630mm



PREMIER
LOFT LADDERS

PREMIER LOFT LADDERS
2 Dawson Drive,
Trimley St Mary,
Felxstowe, Suffolk. IP11 0YW
www.premierloftladders.co.uk

Tel: 0845 9000 195
Fax: 01394 214413



© All rights reserved

Report all discrepancies

Do not scale drawings

Other sizes and different ceiling heights are available on request		Date	Name	Wooden Fire Rated Loft Hatch F30, F30 Plus, F60	Scale 1:10 AT A1
		09.05.2018	JP		
	6000498			The data on the drawings is for information only. All dimensions must be checked on site. No responsibility is taken for errors.	