



Piccolo Premium Vertical

Ready to install element

Stairs:

Scissor unit and treads: Aluminium

Load bearing capacity per tread: 150kg or 350kg/m² of the entire component.

Tread depth: 8cm

Standard sizes:

Available in four height and two width options.

Refer to tables below for details.

40mm clearance from edge of aperture. 80mm clearance available on special request.

Aperture size (width) min. cm	Tread width
from 40	28
from 45	33

Piccolo Premium Vertical

Aperture length depends on the number of treads		Space required in cm	
Treads	Aperture size (length) min. cm	Floor to floor height "A"	Setdown point with $\alpha = 20^\circ$ "B"
9	71	200 - 225	82 - 91
10	78	225 - 250	91 - 100
11	82	250 - 275	100 - 109
12	86	275 - 300	109 - 118



PREMIER LOFT LADDERS
2 Dawson Drive,
Trimley St Mary,
Felixstowe, Suffolk. IP11 0YW
Tel: 0345 9000 195
Fax: 01394 214413
www.premierloftladders.co.uk



© All rights reserved. Report all discrepancies. Do not scale drawings.

First	Date	Name	Scale

Other sizes and different ceiling heights are available on request

6000417

The data on the drawings is for information only. All dimensions must be checked on site. No responsibility is taken for errors.