



**Elite with backboard**

**Ready to install element**

**Safety tested:** Tested according to DIN EN 14975 by TÜV Süd

**Stairs:**

Scissor unit: Aluminium  
 Load bearing capacity per tread: 200kg or 500kg/m<sup>2</sup> of the entire component.  
 Tread depth: 14cm

**Standard sizes:**

Available as standard with a tread width of 350mm, suitable for a minimum aperture width of 580mm. 12 tread stairs have a maximum tread width of 300mm, suitable for a minimum aperture of 530mm.

**Custom sizes:**

Custom sizes are available on request. Please refer to custom width table below

Aperture length depends on the number of treads		Space required in cm	
Treads	Aperture size (length) min. cm	Floor to ceiling height "A"	Setdown point with $\alpha = 20^\circ$ "B"
8	59	190 - 220	94 - 102
9	62	221 - 250	105 - 113
10	67	250 - 279	116 - 124
11	75	279 - 309	126 - 134
12	82	309 - 339	137 - 145

Custom widths	
Aperture size (width) min. cm	Tread width
43	20
48	25
53	30
58	35
61	38



PREMIER LOFT LADDERS  
 2 Dawson Drive,  
 Trimley St Mary,  
 Felixstowe, Suffolk. IP11 0YW  
 Tel: 0345 9000 195  
 Fax: 01394 214413  
 www.premierloftladders.co.uk

Other sizes and different ceiling heights are available on request	Date	Name	Elite with wooden backboard	Scale 1:10
	C 27.07.2017	JP		
	D 02.10.2019	JP		
	E 04.05.2020	JP		
6000231	The data on the drawings is for information only. All dimensions must be checked on site. No responsibility is taken for errors.			

NOTE: ALL INFORMATION CONTAINED IN THIS DOCUMENT IS STRICTLY CONFIDENTIAL. THIS DRAWING IS THE PROPERTY OF PREMIER LOFT LADDERS AND MUST NOT BE REPRODUCED WITHOUT PRIOR PERMISSION.