



Supreme with wooden hatchbox - Vertical Access

Thermal properties: U-Value = 0.58 W/m²K
 Calculated by manufacturer according to DIN EN ISO 6946

Stairs:
 Scissor unit: Aluminium
 Load bearing capacity per tread: 200kg or 500kg/m² of the entire component.
 Tread depth: 14cm

All stair units area made to measure

Treads	Aperture size (height)	Space required in cm		
		Floor to ceiling height "A"	Touchdown point "B"	Swivel range "C"
9	80 - 149	220 - 250	119 - 102	133
10	85 - 149	250 - 279	127 - 109	144
11	95 - 149	279 - 309	135 - 124	155
12	105 - 149	309 - 339	142 - 129	166
Hatchbox external dimensions = aperture size -2cm				



PREMIER LOFT LADDERS
 2 Dawson Drive,
 Trimley St Mary,
 Felixstowe, Suffolk. IP11 0YW
 Tel: 0345 9000 195
 Fax: 01394 214413
 www.premierloftladders.co.uk

© All rights reserved		Report all discrepancies		Do not scale drawings	
	Date	Name	Supreme with wooden hatchbox - vertical access	6000238	Scale 1:10
A	14.09.2013	JP			
B	10.06.2014	JP			
C	10.06.2020	JP	The data on the drawings is for information only. All dimensions must be checked on site. No responsibility is taken for errors.		