



## Supreme DD

Ready to install element

**Safety tested:** Tested according to DIN EN 14975 by TÜV Süd

**Airtightness (a value):** class 4 - 600 pa pressure tested to DIN EN 12207 / 12144 by IFT Rosenheim

**Thermal properties:** U-Value = 0.29 W/m<sup>2</sup>K  
Calculated by the manufacturer according to DIN ISO 6946

### Stairs:

Scissor unit: Aluminium

Load bearing capacity per tread: 200kg or 500kg/m<sup>2</sup> of the entire component.

Tread depth: 14cm (16cm)

### Custom sizes:

Custom sizes are available on request.

### Electric operation:

Electric operation available. Minimum aperture sizes differ to those shown below.

Details available on request.

Aperture length depends on the number of treads		Space required in cm		
Treads	Aperture size (length)	Floor to ceiling height "A"	Setdown point "B"	Swivel range "C"
9	90 - 160	220 - 250	133 - 122	140
10	90 - 160	250 - 279	144 - 133	152
11	90 - 160	279 - 309	155 - 143	164
12	100 - 160	309 - 339	166 - 154	176
13	130 - 160	339 - 369	194 - 183	203
14	140 - 160	369 - 399	206 - 194	216
15	150 - 160	399 - 430	218 - 205	230

Hatchbox external dimensions = aperture size -2cm

**PREMIER**  
LOFT=LADDERS

PREMIER LOFT LADDERS  
2 Dawson Drive,  
Trimley St Mary,  
Felixstowe, Suffolk. IP11 0YW  
Tel: 0345 9000 195  
Fax: 01394 214413  
www.premierloftladders.co.uk



First Issue	Date	Name	Scale
A	05.2018	JP	1:10
A	07.2020	JP	AT A1

Other sizes and different ceiling heights are available on request

7000201

Supreme with wooden hatchbox

The data on the drawings is for information only. All dimensions must be checked on site. No responsibility is taken for errors.