



Supreme Electric with wooden hatchbox

Ready to install element

Safety tested: Tested according to DIN EN 14975 by TÜV Süd

Airtightness (a value): class 4 - 600pa pressure tested to DIN EN 12207 / 12114 by IFT Rosenheim

Thermal properties: U-Value 0.58 W/m²K
Calculation of the isolated are according to DIN ISO 12567-1 by IFT Rosenheim

Stairs:
Scissor unit: die-cast aluminium
Load bearing capacity per tread: 200kg or 500kg/m² of the entire component.
Tread depth: 14cm (16cm)

Custom sizes:
Custom sizes are available on request

Aperture length depends on the number of treads		Space required in cm		
Treads	Aperture size (length)	Floor to ceiling height "A"	Setdown point "B"	Swivel range "C"
9	110 - 160	220 - 250	139 - 128	146
10	120 - 160	250 - 279	151 - 139	159
11	130 - 160	279 - 309	162 - 150	171
12	140 - 160	309 - 339	174 - 161	184
13	145 - 160	339 - 369	202 - 190	212
14	150 - 160	369 - 399	215 - 203	225
15	155 - 160	399 - 430	227 - 214	239

Hatchbox external dimensions = aperture size -2cm

Standard sizes		
Aperture size length x width	Hatchbox height	Tread width
120 x 70 cm	24 cm	30 cm
130 x 70 cm	24 cm	30 cm
140 x 70 cm	24 cm	30 cm



PREMIER LOFT LADDERS
2 Dawson Drive,
Trimley St Mary,
Felixstowe, Suffolk. IP11 0YW
Tel: 0345 9000 195
Fax: 01394 214413
www.premierloftladders.co.uk

Other sizes and different ceiling heights are available on request	Date	Name	Supreme Electric with wooden hatchbox	Scale 1:10
	12.07.2017	JP		
	24.08.2020	JP		
6000455		The data on the drawings is for information only. All dimensions must be checked on site. No responsibility is taken for errors.		

NOTE: ALL INFORMATION CONTAINED IN THIS DOCUMENT IS STRICTLY CONFIDENTIAL. THIS DRAWING IS THE PROPERTY OF PREMIER LOFT LADDERS AND MUST NOT BE REPRODUCED WITHOUT PRIOR PERMISSION.