



Elite Vertical

Ready to install element

Safety tested: Tested according to DIN EN 14975 by TÜV Süd

Stairs:
 Scissor unit: Aluminium
 Load bearing capacity per tread: 200kg or 500kg/m² of the entire component.
 Tread depth: 14cm

Standard sizes:
 Available in five height and five width options. Refer to tables below for details.
 40mm clearance from edge of aperture. 80mm clearance available on special request.

Aperture length depends on the number of treads		Space required in cm	
Treads	Aperture size (length) min. cm "C"	Floor to ceiling height "A"	Setdown point with $\alpha = 20^\circ$ "B"
8	75	190 - 220	94 - 102
9	78	220 - 250	99 - 108
10	83	250 - 279	110 - 118
11	91	279 - 309	120 - 129
12	98	309 - 339	130 - 140

Custom widths	
Aperture size (width) min. cm	Tread width
46	20
51	25
56	30
61	35
64	38

NOTE: ALL INFORMATION CONTAINED IN THIS DOCUMENT IS STRICTLY CONFIDENTIAL. THIS DRAWING IS THE PROPERTY OF PREMIER LOFT LADDERS AND MUST NOT BE REPRODUCED WITHOUT PRIOR PERMISSION.



PREMIER LOFT LADDERS
 2 Dawson Drive,
 Trimley St Mary,
 Felixstowe, Suffolk. IP11 0YW
 Tel: 0345 9000 195
 Fax: 01394 214413
 www.premierloftladders.co.uk

Other sizes and different ceiling heights are available on request	6000453	Elite vertical	Scale 1:10
The data on the drawings is for information only. All dimensions must be checked on site. No responsibility is taken for errors.			