



Cadet 3 Wooden Loft Ladder

Ready to install element

Safety tested:

Tested according to DIN EN 14975 by TÜV Süd

Airtightness (a value):

Class 4 - 600pa pressure tested to DIN EN 12207 / 12114 by IFT Rosenheim

Thermal properties:

U-Value lower cover = 0.90 W/m²K. Certified according to DIN ISO 12567-1 by IFT Rosenheim

Stairs:

Wooden ladder: 3-part folding
 Load bearing capacity per tread: 150kg
 Tread dimensions: 36cm x 8cm

Space required in cm			
Aperture size (length x width)	Floor to ceiling height "A"	Setdown point "B"	Swivel range "C"
120 x 60	220 - 288	88 - 128	168
120 x 70	220 - 288	88 - 128	168
130 x 70	220 - 288	88 - 128	168
140 x 70	220 - 288	88 - 128	168
Hatchbox external dimensions = aperture size - 2 cm			



PREMIER LOFT LADDERS
 2 Dawson Drive,
 Trimley St Mary,
 Felixstowe, Suffolk. IP11 0YW
 Tel: 0345 9000 195
 Fax: 01394 214413
 www.premierloftladders.co.uk

© All rights reserved. Report all discrepancies. Do not scale drawings.		Date		Name		Scale	
FIRST ISSUE		18.06.2020		JP		1:10	
A		08.03.2024		JP		Cadet 3	
Other sizes and different ceiling heights are available on request		6000500		The data on the drawings is for information only. All dimensions must be checked on site. No responsibility is taken for errors.			



NOTE: ALL INFORMATION CONTAINED IN THIS DOCUMENT IS STRICTLY CONFIDENTIAL. THIS DRAWING IS THE PROPERTY OF PREMIER LOFT LADDERS AND MUST NOT BE REPRODUCED WITHOUT PRIOR PERMISSION.