



STANDARD HANDRAIL SUPPLIED ON ONE SIDE ONLY. HANDRAIL BRACKETS INSTALLED AS STANDARD ON BOTH SIDES TO ENABLE INSTALLER TO CHANGE HANDRAIL SIDES OR PURCHASE AND INSTALL AN ADDITIONAL HANDRAIL.

ROOF SPACE FLOOR LEVEL

JOIST OR STRUCTURAL TIMBER

A SPACER (ILLUSTRATED) OF APPROX. 50mm WILL BE REQUIRED WHERE THE VERTICAL FIXING SURFACE EXCEEDS THE HEIGHT OF THE BACKBOARD TO A POINT WHERE THE LADDER WOULD FOUL AGAINST THE SURFACE WHEN STOWED. SPACER AVAILABLE AS AN OPTIONAL ACCESSORY.

CEILING LEVEL

MAXIMUM HEIGHT UP TO 3390 mm (FLOOR TO BOTTOM OF BACK MOUNTING BOARD)

NOTE:
IT IS RECOMMENDED THAT THE MINIMUM STRUCTURAL OPENING LENGTH IS 1000 mm FOR AN ELITE STAIRWAY INSTALLED WITH A HANDRAIL.

PREMIER LOFT LADDERS
2 Dawson Drive
Trimley St. Mary
Felixstowe
Suffolk
IP11 0YW

www.premierloftladders.co.uk
Tel: 0845 9000 195



Issue status:			
Issue	Description	Date	Name
D	Revised foot	02/2023	J.P.
C	Add standard handrail	08/2016	J.P.
B	Logo change	08/2014	J.P.
A	Addition of packer text	09/2013	J.P.
	First issue	10/2012	J.P.

Drawing Title:		Scale:
ELITE STAIRWAY: 12 treads		1:1
Sheet:		PLOT AT
A3 1:5		Issue:
D		
All dimensions in mm		
© All rights reserved Report all discrepancies Do not scale drawings		
Filename:	ELITE12 HANDRAIL.DWG	Project: Standard Issue